

## SECTION 09/GUIDE SPECIFICATIONS DYNAPOINT 14 + 3 POLYURETHANE FLOOR SYSTEM

### Part 1 - GENERAL DESCRIPTION

#### 1.01 DESCRIPTION

##### A. Scope

1. The complete installation of **DYNAPOINT 14+3** polyurethane surfacing over polyurethane / rubber granulate base, by Caliber Sport Systems Inc, including adhesives, base mat, polyurethane sealer, polyurethane resin, surface finish, and game lines.
- B. Related work specified under other sections: (A cross-reference should be incorporated in these sections)
  1. Substrate Buildup:
    - a. Asphalt for outdoor or indoor installations
    - b. Concrete for indoor installations..... Section 03300
  2. Slab Depression
    - a. Depression shall be thickness equal to total thickness of base mat 14 mm and polyurethane layers (3 mm.).
  3. Slab Tolerance
    - a. Slab tolerance is (+/-) 1/8" in radius of 10'. surface steel troweled.
    - b. **NO CURING AGENTS OR SEALERS ARE TO BE APPLIED TO THE CONCRETE SLAB.**
  4. Membrane waterproofing and damp-proofing..... Section 07100
    - a. Concrete subfloors on or below grade shall be adequately waterproofed beneath and at the perimeter of the slab and on the earth side of below-grade walls.
  5. Thresholds: metal..... Section 08700
  6. Game standard inserts..... Section 11500

#### 1.02 QUALITY ASSURANCE

##### A. Supplier Qualifications

1. Supplier shall be an established firm experienced in field: Caliber Sport Systems Inc., or an approved equal.
2. Formulator shall be **ISO-9001 and ISO-14001** Certified, and provide copy of Certification document upon request.

##### B. Installer Qualifications

1. Flooring contractor shall be experienced in he flooring field and approved by Supplier.
2. Flooring contractor shall be factory-approved and have completed at least three projects of similar magnitude and complexity.
3. Submit three copies of supplier's recommendations for correct preparation, finishing and testing of concrete subfloor surface to receive granulated base mat and polyurethane floor system.

#### 1.03 SUBMITTALS

- A. Supplier's Product Data: Submit one copy
- B. Samples: Submit one sample of **DYNAPOINT 14+3** System
- C. Maintenance Literature: Submit copy of **DYNAPOINT** maintenance instructions.

#### **1.04 DELIVERY AND STORAGE**

##### A. Delivery of Materials

1. Material shall not be delivered or installed until all masonry, painting, plastering, tile work, marble and terrazzo work are completed, and all overhead mechanical work, lighting, backstops, scoreboards are installed. Room temperature shall be at least 55 degrees Fahrenheit and moisture content of concrete slab of 3% or less.
2. Area where materials are to be stored should be maintained at 55 degrees Fahrenheit and under 50% relative humidity by the General Contractor.

#### **1.05 JOB CONDITIONS**

##### A. Schedule of Installation

1. Do not install floor system until concrete has been cured sixty (60) days, and the conditions in Paragraphs 1.01 and 1.04 are obtained.
2. Environmental temperatures must average a minimum of 65 degrees Fahrenheit for one full week preceding, throughout, and 72 hours following application.
3. After **DYNAPOINT** sports surface is installed and game lines are painted, area is to be kept locked by General contractor to allow curing time for the paint and finish system(s). No other trades are to be allowed on floor until it is accepted in writing by owner or owner's authorized agent.

#### **1.06 GUARANTEE**

- A. Guarantee shall not cover damage caused in whole or in part by casualty, ordinary wear and tear, abuse, use for which material is not designed, faulty construction of the building, settlement of the building walls, failure of the other contractors to adhere to specifications, separation of the concrete slab and excessive dryness or excessive moisture from humidity, spillage, mechanical failure, migration through the slab or wall, or any other source.
- B. Caliber Sport Systems Inc. hereby warrants **DYNAPOINT** to be free from manufacturing defects for a period of one (1) year. This warranty is in lieu of all other warranties, expressed or implied, including but not limited to any warranty of merchantability or fitness for a particular purpose, and of any other obligations on the part of Caliber Sport Systems Inc. in the event of breach of any warranty, the liability of Caliber Sport Systems Inc. shall be limited to repairing or replacing **DYNAPOINT** material as supplied by Caliber Sport Systems Inc., and proved to be defective in manufacture, and shall not include any other damages, either direct or consequential.

### **PART 2 – PRODUCTS**

#### **2.01 MATERIALS**

**NOTE: USE OF ANY NON-APPROVED COMPONENT SUBSTITUTIONS SHALL VOID WARRANTY.**

##### A. **DYNAPOINT 14+3**

1. Adhesive
  - a. Polyurethane Adhesive: a two-component polyurethane
2. Shock Pad
  - a. Granulated rubber/foam/polyurethane mat 14 mm thick
3. Pad Sealer
  - a. Dynapoint Pad Sealer: a two-component polyurethane sealer

4. Polyurethane Resin
  - a. Dynapoint PUR Polyurethane Wear Coating, a two-component polyurethane (1 mm)
  - a. Dynapoint PUR Polyurethane Wear Coating, a two component polyurethane (2 mm)
5. Coating
  - a. DYNAPOINT TUFF COAT: a pigmented two-component polyurethane surface paint
6. Game line Paint
  - a. DYNAPOINT Line paint: a pigmented two-component polyurethane paint

**B. Technical Information**

- Shock Absorption (DIN 18032) 14 +3 35%  
0.52
- Friction (ASTM D-1894) Dry >99%
- Ball Rebound (DIN 18032) 80 Shore A (+1-5)
- Surface Hardness (ASTM D-2240)
- Structure layer properties 1,275 psi
- Tensile strength 240%
- Elongation at break (DIN 53455) 130pli
- Tensile strength of Top Layer (DIN 51960) Class 1/Not Flammable

**PART 3 – EXECUTION**

**3.01 INSPECTION**

- A. Inspect concrete (or asphalt / or wood) substrate for dryness, proper tolerance, and possible contamination, (see Part 1-Sec 1.01 and Sec 1.04) and report any discrepancies to General Contractor in writing.
- B. All work required to put concrete (or other) substrate in acceptable condition shall be the responsibility of the General Contractor.
- C. Substrate shall be broom cleaned by the General Contractor.
- D. Installer shall perform tests for moisture and adhesion prior to application and report adverse conditions to the general contractor in writing.

**3.02 INSTALLATION**

**A. DYNAPPOINT 14+3**

1. Mix two-component DYNAPOINT Adhesive according to supplier's directions and spread adhesive using 3/32" notched trowel.
2. Unroll polyurethane/rubber granulated base mat into freshly applied adhesive. Seams shall be in virtual contact with absence of compression fit. Roll surface of base mat with a medium-size roller.
3. Mix two-component Pad Sealer according to supplier's directions and spread sealer over base mat using a straight trowel. Allow to cure minimum 12 hours before proceeding.

4. Mix two-component DYNAPPOINT PUR pigmented polyurethane resin and apply at proper thickness (0.5mm) in accordance with supplier's instructions. Allow to cure minimum 12 hours before proceeding.
  5. Mix two-component DYNAPPOINT PUR pigmented polyurethane resin and apply at proper thickness (1.5mm) in accordance with supplier's instructions. Allow to cure minimum 12 hours before proceeding.
  6. Mix two-component DYNAPPOINT TUFF COAT and apply using lint free roller. Allow 24 to 48 hours curing time before proceeding.
- B. Game Lines
1. Mix two-component DYNAPPOINT Line striping paint in accordance with supplier's instructions.
  2. Line painting should be in accordance with supplier's directions.
  3. Color of game lines shall be chosen from DYNAPPOINT standard colors
  4. Consult architectural drawings for game line locations and chosen colors.
- C. Perimeter Molding (Optional): Install a rubber base, anchored to the walls with standard base cement.
- D. Clean up all unused materials and debris and remove from the premises. Dispose of empty containers in accordance with federal and local regulations.

### **3.03 PROTECTION**

- A. Cure Time
1. No traffic or other trades shall be allowed on the surface for a period of one week following completion to allow for complete and proper cure of the finish.
- B. Other Trades
1. It shall be the responsibility of the general contractor to protect the surface from damage by other trades before acceptance by the owner or the owner's authorized agent.
- C. Safety
1. No smoking, open flames or sparks from electrical equipment or any other source shall be permitted during the installation process, or in areas where materials are stored.