



Bona Sport[®]
Waterborne and Oil-Modified Finishes

Waterborne Finishes

Bona Sport® waterborne finishes are used on many high-profile floors across the world. They give the facility peace of mind knowing they are getting the durability and chemical resistance necessary, while being a sustainable, healthy option for those working on these floors.

Finish Base | Water

Resin | Polymeric

Intercoat Abrasion | No abrasion needed*



Bona SuperSport **ELITE**™

Two-component

VOC g/L **275**

Solids **32%**

Coverage/
Gallon **450-550**
sq.ft.

Durability

Dry Time **2-3****HRS

Leveling

NEW



Bona SuperSport **MVP**™

Two-component

VOC g/L **275**

Solids **30%**

Coverage/
Gallon **500-600**
sq.ft.

Durability

Dry Time **2-3****HRS

Leveling

NEW



* No abrasion needed if coated within 48 hours of initial coat

** Environmental jobsite conditions (Temp and RH) can vary dry times

GOOD

BETTER

BEST



Bona® SuperSport

Two-component

VOC g/L	350	Solids	28%
Coverage/ Gallon	500-600 sq.ft.	Durability	■ ■ ■
Dry Time	2-3** HRS	Leveling	■ ■ ■ ■



Bona SuperSport **DRIVE**®

One-component

VOC g/L	275	Solids	28%
Coverage/ Gallon	500-600 sq.ft.	Durability	■ ■ ■
Dry Time	2-3** HRS	Leveling	■ ■ ■ ■



Bona SuperSport **ONE**®

One-component

VOC g/L	200	Solids	32.5%
Coverage/ Gallon	500-600 sq.ft.	Durability	■ ■
Dry Time	2-3** HRS	Leveling	■ ■ ■ ■



* No abrasion needed if coated within 48 hours of initial coat
 ** Environmental jobsite conditions (Temp and RH) can vary dry times



Oil-Modified Finishes

Bona Sport® oil-modified finishes have been proven to provide a tough, durable coat to wood sport floors. They give a slight amber color preferred by some facilities.

Finish Base | Oil

Resin | Oil-Modified Polyurethane

Intercoat Abrasion | Needed



Bona Sport® Poly 275

VOC g/L	275	Solids	57-59%
Coverage/ Gallon	600 sq.ft.	Durability	
Dry Time	18-24** HRS	Leveling	



Bona Sport® Poly 350

VOC g/L	350	Solids	52-55%
Coverage/ Gallon	600 sq.ft.	Durability	
Dry Time	18-24** HRS	Leveling	



Bona Sport® Poly

VOC g/L	450	Solids	50%
Coverage/ Gallon	600 sq.ft.	Durability	
Dry Time	12-16** HRS	Leveling	



Bona All Court® Poly

VOC g/L	500	Solids	43%
Coverage/ Gallon	600 sq.ft.	Durability	
Dry Time	8-12** HRS	Leveling	



* No abrasion needed if coated within 48 hours of initial coat

** Environmental jobsite conditions (Temp and RH) can vary dry times

GOOD

BETTER

BEST